

| Common Name: | Ti-6Al-4V Ti-6-4 | Titanium Grade 5 |
|----------------------|---|---|
| UNS Number: | R56400 | |
| General Information: | the most common of al goods. The wrought moderate strength, goo | most widely used titanium alloy of the alpha-plus-beta class, and is also I titanium alloys. The alloy is castable and is utilized "as cast" in sporting material is used in aerospace, medical, and other applications where d strength to weight, and favorable corrosion properties are required. The tings, wire, bar, plate, sheet, forgings, rings, and billet. |

| Common Specifications: | Specification: | Product Form: | | |
|------------------------|-------------------------|--|--|--|
| - | AMS 4911 | Strip, Sheet, and Plate, Annealed | | |
| | AMS 4920 | Forgings, Alpha-Beta or Beta Processed, Annealed | | |
| | AMS 4928 | Bar, Wire, Forgings, Ring, Annealed | | |
| | AMS 4965, AMS 4963, and | Bar, Wire, Forgings, Ring, Solution | | |
| | AMS 4967 (Capable of) | Treated & Aged | | |
| | AMS-T-9047 | | | |
| | ASTM B348 (Grade 5) | Bar and Billet, Annealed | | |
| | ASTM B367 (Grade 5) | Castings | | |
| | ASTM F1472 | Wrought Alloy for Surgical Implants | | |
| | AWS A5.16 (ERTi-5) | Weld Wire | | |

| Chemistry Requi | rements: | % Maxim | um unless gi | ven as a rang | ge. | | | | |
|--|----------|---------|--------------|---------------|-----|----------|---------|-------|---------|
| | Ν | С | Н | Fe | 0 | Al | V | Y | Ti |
| | 0.05 | 0.08 | 0.125 | 0.40 | 0.2 | 5.5-6.75 | 3.5-4.5 | 0.005 | Balance |
| Note: Chemical requirements are not consistent between specifications. Check referenced specifications | | | | | | | | | |

Minimum Tensile Properties:

| Condition | UTS ksi (Mpa) | 0.2%YS ksi (MPA) | % El. | % RA* |
|---------------------------|------------------|---------------------|-------|-------|
| As specified (shape) | 130 (895) | 120 (828) | 10 | 25 |
| Solution Treated and Aged | 160 (1103) | 150 (1034) | 10 | 20 |
| Castings | 130 (895) | 120 (828) | 6 | 10 |

Note: Mechanical properties vary with diameter. Check referenced specifications.

Typical Tensile Properties:

| Condition | UTS ksi | 0.2%YS ksi | % El. | % RA* |
|---------------------------|------------|------------|-------|-------|
| | (Mpa) | (MPA) | | |
| Annealed | 145 (1000) | 132 (910) | 18 | 40 |
| Solution Treated and Aged | 161 (1110) | 141 (970) | 15 | 45 |
| Castings | 145 (1000) | 130 (895) | 5 | 15 |

Note: Typical properties are not to be utilized as a requirement, but are only listed for guidance. These properties may or may not be attainable in all circumstances.

* %Ra not required by all specifications